



# The VP2020

Digital Color Label Printer



inkjet  
technology by 



## VP2020 Specifications

<b>Print technology</b>	Powered by HP Inkjet Technology
<b>Print resolution</b>	600x600 or 300x600 (dpi)
<b>Throughput examples in color*</b>	Draft mode: up to 1.45 IPS Normal mode: up to 0.77 IPS High mode: up to 0.44 IPS Premium mode: up to 0.21 IPS
<b>Special features</b>	Manual stock cutter module Internal web page for supplies forecasting and diagnostics
<b>Built-in ROM</b>	8MB Flash: expandable to 32MB (SIMM Module)
<b>Built-in RAM</b>	64 SDRAM: expandable to 128MB (DIMM Module)
<b>Interfaces</b>	USB (V1.1) Ethernet (10 base T) Synchronization port for connection to external accessories Optional wireless Ethernet (802.11b)
<b>Printer/user interaction</b>	Back lit display, indicator lights and operator menu Informational messages sent via the driver and e-mail Printer internal web page accessed via standard internet browse
<b>Printer security</b>	Multiple level operator menu structure Printer web page password controlled
<b>Electrical</b>	Universal power supply 98VAC/240VAC at 50Hz/60Hz maximum
<b>Standards</b>	FCC, CE CSA <sup>1</sup> , TUV, GS
<b>Media sensing</b>	Gap Continuous Black mark
<b>Label roll sizes</b>	3" internal core 8" external roll size Maximum width 6.15 inches
<b>Stock loading</b>	Stock roll loaded from the front of the unit Stock roll protected from dust and pollutants Open, accessible stock path Stock roll and printing path visible to operator
<b>Character fonts/sets</b>	Auto font caching Downloadable fonts (TrueType)
<b>Bar code symbologies</b>	Code 39, Code 93, UCC 128 Code 128 auto select Codabar, EAN-128 Interleaved 2 of 5 UPC-A UPC-E, EAN-8, EAN-13 POSTNET, Maxicode, PDF-417
<b>Operating systems supported by driver and software</b>	Microsoft Windows XP, 98, 98SE, ME, NT 4.0 workstation, NT 4.0 server, 2000 professional, 2000 server, 2000 advanced server
<b>Label Software</b>	Bartender™ by Seagull Scientific™ *Inclusion of light version software extended functionality for a 30-day trial period
<b>Dimensions</b>	Height=18" (450mm), Width=24" (610mm), Depth=17" (425mm)
<b>Weight</b>	94.2lbs (41.9KG)

VIPCOLOR TECHNOLOGIES USA, INC. ■ 6701 MOWRY AVENUE, NEWARK, CA 94560

Toll free: 800-404-3185 ■ Fax: 510-744-3738 ■ info@vipcolor.com



VIPColor withholds the right to change unit specifications without prior notice or consent. VIPColor is a trademark of VIPColor Technologies USA, Inc. a member of Venture Corporation Limited ([www.venture-mfg.com.sg](http://www.venture-mfg.com.sg)) © 2002, VIPColor Technologies USA, Inc.  
<sup>1</sup>Both UL and CSA are now recognized by all federal, state, provincial and local authorities to test and certify product-safety in the U.S. and Canada.

\*Speed is dependant on label width, print direction, and image. All speeds quoted are based on 6" width.

Printed 08/2002